

Professional Installation Projectors

6700 Series

Ideal for corporate, higher education and museum applications



Powerful installation projectors equipped to take on the most demanding integration projects

Powerful Tools

- Multi-display support with Picture by Picture/Picture Out Picture
- TileMatrix (internal multi-screen splitter) enables 4Kx2K resolution utilizing 4 projectors without the need for external hardware
- Built-in daisy chain capabilities support multi-display applications
- Seamlessly blend multiple images with integrated edge blending capabilities

Integrated

- High performance video processing/scaling creates life-like images
- Integrated software applications such as Crestron Roomview, AMX Beacon and PJ Link allow for complete interactivity and control


Flexible

- Enjoy greater installation flexibility with a complete line of optional bayonet style lenses (6) for quick and easy exchange. Lens throw distances range from 2.5 to 68.5 ft
- Tilt-free installation capabilities make these projector ideal for almost any install environment, including portrait orientation
- Up to 60% vertical lens shift and +/- 30% horizontal lens shift capabilities make alignment easy

Screen Splitter


DUKANE is committed to bringing the latest and greatest innovation to projectors. Multi-display capabilities and TileMatrix technologies are integrated into the new 6700 Series projectors. This processing is all done internally and therefore eliminates the additional hardware typically required to produce a beautiful 4K resolution image.

Screen Splitter (Multi Display) by Daisy Chain



Stacking correction

The industry's first built-in stacking correction capabilities (up to four projectors) allows the projectors to boost an image's brightness up to 24,800 lumens, which is ideal for larger-sized screens and environments with heavy ambient light. This feature also prevents the complete loss of an image, which can happen when using only one projector.



Edge blending

This function seamlessly blends multiple projected images to display a single high-resolution image.




Dual HDMI inputs

Among the 6700 Series' wide selection of inputs are dual HDMI w/ HDCP for connecting to high-definition sources such as Blu-ray players, cable boxes, satellite receivers and personal computers. With multiple HDMI connections, loop out up to four projectors.



INTEGRATED NETWORKING AND ASSET MANAGEMENT

- Integrated RJ45 connection for quick connection to the LAN (10/100 base-T capability)
- Optional high-speed wireless LAN IEEE 802.11b/g/n
- Desktop control allows you to securely transmit information wirelessly to the projector from a docking station or PC in another room
- Image Express Utility (IEU 2.0; compatible with Windows or Mac operating systems) dedicated projector software provides wired and wireless data transmission via peer-to-peer or over the network
- Broadcast mode allows you to send information from one computer to several projectors
- Windows Network Projector function within Windows Vista connects directly to networked projectors without the need for additional proprietary software
- Windows Remote Desktop function allows you to control a networked computer by connecting a USB mouse and keyboard directly to the projector's USB input
- Windows Network Drive Function displays multimedia files (.jpeg, .bmp, .png, .mpeg2 or .wmv9) in the Windows shared folder on a local network using the Viewer function—all without bringing your PC into the conference room
- Windows Media Connection Function displays multimedia files (.mpeg2, .jpeg or .wmv9) stored on the Windows Media Connect server or a local network using the Viewer function—all without bringing your PC into the conference room
- Crestron Roomview Connected™



GET CONNECTED WITH A WIDE SELECTION OF INPUTS

- **Dual computer inputs** ensure quick switching between presentations
- **Four audio inputs (two mini stereo [Comp1 & Comp2] and HDMI™)** make it easy to add sound to enhance your presentations

Remote control

Wired and wireless backlit remote allows you to adjust for complete control of the projectors menu structure in a well lit or dark environment. Direct controls such as lamp mode, aspect ratio, volume and input selection eliminates multiple button pushes.



DisplayPort

This input provides 6700 Series models with expanded connectivity with advanced technology.



Wall color correction presets

These provide for adaptive color tone correction to display properly on non-white surfaces.

On a green wall...



BEFORE auto wall correction



AFTER auto wall correction



Input panel cover

This optional accessory creates a clean look for your installation, while hiding signal cables and the power cord.



ADVANCED SOFTWARE FEATURES

Cornerstone

Enhanced keystone correction allows for horizontal, vertical and diagonal image correction for aligned images even when the projector is set up at an angle to the screen.




3D

When combined with active shutter glasses and 3D emitter, the 6700 Series Projectors create 3D images from a computer or Blu-ray player. The 6757W/6752WU/6762 utilize the 3D sync line output from the projector to connect to the 3D emitter. Optional 3D glasses and emitters from XPAND are available from DUKANE.



Geometric Correction

Projecting an image isn't confined to a standard flat screen or wall with the DUKANE 6700 Series. Geometric correction allows these models to project an image on spheres, cylinders, corner angles and many more non-standard surfaces.



4000-hour filter life

DUKANE is committed to designing its products to provide long lifecycles. This virtually maintenance-free filter reduces the frequency at which cleaning is required, thereby decreasing total cost of ownership.




Tilt-free


The projector can be rotated freely (360°) to orient the image depending on the installation requirements



Portrait mode

Allows the projector to be rotated (and screen if necessary) to a vertical alignment so that portrait content can be viewed without black bars on the side when landscape mode is used.





UNIQUE FEATURES

3D Reform™ allows you to square the image by adjusting horizontally, vertically or diagonally when the projector cannot be placed parallel or perpendicular to the screen

Virtual Remote Used via a network connection (wired/ wireless), you can control the projector directly from a computer without the need for additional control cables.

Variable audio-out enables the remote control to be used to adjust volume of self-powered external speakers that are connected to the projector. In stand-by mode, the audio-out stays active, allowing the last input used to pass to the self-powered external speakers.

Advanced AccuBlend™ ensures detailed images when non-native resolution sources are connected to the projector

AutoSense™ automatically syncs with any computer signal and features one-touch image optimization

64-step image magnification with location control

Discreet source keys for source selection

Remote diagnostics enable the user to monitor and make adjustments to the projector remotely

Built-in HTTP page for control and monitoring over a LAN network. Email notification of error messages or lamp end-of-life can be sent to remote locations.

WARRANTY

Three (3) year limited warranty

IN THE BOX

Remote control, batteries, power cord, RGB signal cable, lens cap, user's manual on CD-ROM, quick start guide, product registration card, wired and wireless network setup guide.

ORDERING MODEL NUMBERS

6757W
6752WU
6762

Specifications for 6757W/6752WU/6762

OPTICAL Display Technology Light Output (lumens) Resolution Native Maximum Contrast Ratio (up to) Lamp Type Lamp Life (up to) Screen Size (diagonal) Throw Ratio NP11FL NP12ZL NP13ZL NP14ZL NP15ZL NP30ZL Projection Distance Projection Angle Lens* Zoom Zoom Ratio Focus F-number, f-number NP11FL NP12ZL NP13ZL NP14ZL NP15ZL NP30ZL Shift Keystone Correction	6757W: 0.75" LCD with MLA 6752WU: 0.76" LCD with MLA 6762: 0.79" LCD with MLA 6757W: 5700 normal 6752WU: 5200 normal 6762: 6200 normal 6757W: WXGA 1280 x 800 6752WU: WUXGA 1920 x 1200 6762: XGA 1024 x 768 WUXGA 1920 x 1200 6000:1 with auto iris 350W AC / 264W eco 3000 hours normal / 4000 hours eco 40 to 500 in. / 1.02 to 12.7m 0.80:1 1.19 - 1.56:1 1.50 - 3.02:1 2.97 - 4.79:1 4.70 - 7.02:1 0.79 - 1.04:1 2.5 to 68.5 ft. / 0.74 to 20.9m 10.3 to 10.8° tele / 13.7 to 14.5° wide Manual NP11FL: NA / NP12ZL: 1 to 1.31 / NP13ZL: 1 to 2.01 / NP14ZL: 1 to 1.61 / NP15ZL: 1 to 1.53 / NP30ZL: 1 to 1.3 Manual F= 2.3, f= 13.2mm F= 2.2 to 2.69, f= 19.4 to 25.3mm F= 1.7 to 2.37, f= 24.2 to 48.6mm F= 2.2 to 2.64, f= 48.5 to 77.6mm F= 2.2 to 2.7, f= 76.8 to 116.5mm F= 1.9 to 2.1, f= 13.2 to 17.2mm 6752WU/6762: Mechanical -0.1 to +0.5 vertical, +/-0.3 horizontal 6757W: Mechanical -0.1 to +0.6 vertical, +/-0.3 horizontal +/- 40° horizontal, +/- 40° vertical
SIGNAL COMPATIBILITY/CONNECTIVITY Scan Rate Horizontal Vertical Supported Video Standards SD/HD Video Signal Compatibility PC Signal Compatibility Macintosh Compatibility Input/Output Terminals RGB1 (analog) RGB2 (analog) RGB3 (digital) RGB4 (digital) RGB5 (digital) Audio Monitor Out Audio Out 3D Sync Line Audio External Control Sync Compatibility	15 - 153 kHz 48 - 120 Hz NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM 1080p, 1080i, 720p, 576p, 576i, 480p, 480i VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA Yes VGA 15-pin D-sub 5-BNC HDMI w/ HDCP HDMI w/ HDCP DisplayPort w/ HDCP Mini stereo HDMI Mini stereo (Variable audio out) 3Pin D 10W mono RS-232, IR, DDC/CI, USB, Mini Stereo Separate Sync / Composite Sync / Sync on G
ELECTRICAL Power Requirements Input Current Power Consumption (ECO off/ECO Mode/Standby/Standby-Power Saving)	100 - 240V AC, 50/60Hz 5.1A 440W / 362W / 7.4W / 0.11W
MECHANICAL Optional Lenses Installation Orientation Dimensions (WxDxH) Net Weight Fan Noise Regulations	NP11FL, NP12ZL, NP13ZL, NP14ZL, NP15ZL, NP30ZL Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear 19.7 x 14.4 x 6.5 in. / 499 x 366 x 164mm 18.5 lbs. / 8.4 kg 39 dB normal / 33 dB eco USA: UL 1950 FCC Class B, Canada: CSA950 (C-UL), NOM
ENVIRONMENTAL Operating Temperature Humidity Storage	41° - 104°F / 5° - 40°C 20-80% non-condensing -14° - 122°F / -10° - 50°C
ACCESSORIES SCP200 NP3250CM NP11FL NP12ZL NP13ZL NP14ZL NP15ZL NP30ZL 456-6757W NP04CV NP02LM1 RMT-PJ37 PW RCHD-PJPX RGBCBL-PJPX NECECO	Suspended ceiling plate Ceiling mount 0.8:1 fixed short throw lens 1.19 - 1.56:1 zoom lens 1.5 - 3.0:1 zoom lens 2.97 - 4.79:1 zoom lens 4.7 - 7.2:1 zoom lens 0.79 - 1.04:1 zoom lens Replacement lamp Terminal cover Wireless LAN module Replacement remote control Power cable RGB cable Projector recycling program, disposal certificate

* Lens does not ship with the projector.

Additional accessories are available, including screens, carts, mount accessories and replacement cables. Visit www.dukaneav.com for details.



HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

DUKANE CORPORATION

Audio Visual Products
2900 Dukane Drive, St. Charles, IL 60174
Toll-free: 888-245-1966 • Fax: 630-584-5156
E-mail: avsales@dukane.com
www.dukaneav.com

