

Designed for academic achievement in larger classrooms, corporate boardrooms and campus standard.



Key Features

- XGA 1024 x 768 resolution
- 5,000 ANSI lumens white/color output
- 3,000:1 contrast ratio
- Horizontal and vertical lens shift
- 3,000 hours lamp life (Standard mode); 5,000 hours lamp life (Eco mode)*
- 5,000 hours hybrid filter**
- ImageCare Technology for energy savings
- Embedded LAN/wireless compatible
- Projector Quick Connection iOS App

DUKANE CORP

Audio Visual Products
2900 Dukane Drive, St. Charles, Illinois 60174
Toll-free: 888-245-1966 • Fax: 630-584-5156
E-mail: avsales@dukane.com
www.dukane.com/av

Dukane's 8959A combines XGA 1024 x 768 resolution with super-bright 5,000 ANSI lumens white/color light output for a stunning visual achievement. It can transform classrooms, lecture halls, and auditoriums into true learning centers. The 8959A is easily stackable which enables you to place one projector on top of another to project the same image from both onto a screen for added brightness. Plus, Dukane's Intelligent Eco Mode with ImageCare combines optimal picture performance with maximum energy savings for a lower cost of ownership. For added peace of mind, Dukane's 8959A is also backed by a generous warranty and our world-class service and support programs.

8959A



UNIQUE FEATURES

Cloning Function



Copy configuration settings from one projector to others of the same model via USB memory. Cloning can save almost all PJ settings such as gamma and keystone via USB memory.

ImageCare Technology



ImageCare is a lamp power control function that combines optimal picture performance with maximum energy savings by decreasing energy usage, improving contrast ratio and lengthening lamp life. The result is a lower total cost of ownership and decreased maintenance cost.

DICOM® Simulation Mode



Images in DICOM (Digital Imaging and Communications in Medicine) Mode are reproduced with an advanced grayscale level. This mode is ideal for viewing grayscale medical images such as X-rays, and for training and educational purposes.

These projectors are not approved medical devices. They should not be used for actual medical diagnosis.

Intelligent Eco and Saver Modes



Automatically changes the brightness of the lamp according to the brightness level of the screen. Also, automatically changes the brightness of the lamp if there is no change in the screen image. Using ImageCare technology, these features give optimal picture performance with maximum energy savings.

Perfect Fit 2



Enables the user to adjust individual corners and sides independent of one another. Perfect Fit 2 provides vertical and horizontal digital correction of either barrel or pin cushion distortions. This feature helps correct geometric and complicated distortions. Perfect Fit 2 allows the projected image to fit correctly to the screen quickly and easily.

Projector Quick Connection iPad® App



Our iOS application offers full projector control and also provides the capability to display photos, document files and web site contents. Available for iPad® and iPhone® devices. Works over your LAN via your RJ-45 port or via an optional USBWL11N wireless adapter.

Wired and Wireless Switcher Solutions



Multifunctional switcher operates in conjunction with the receiver to provide expanded source selection and switching options for connected devices. The switcher is sold as an optional accessory that can provide 1080p 30 fps wireless via WHDI for both video and audio.


STANDARD FEATURES

Display via USB



Simply plug and play using the USB port instead of the 15 pin D-sub VGA cable.

Easily Stackable



Using the lens shift and the perfect fit you can easily stack two units for two times the light output.

Microphone Input



A microphone can be used via the jack located on the input panel. Allows for more dynamic presentations even in standby mode.

Network Control, Maintenance and Security



Embedded networking gives you the ability to manage and control multiple projectors over your LAN. Features include scheduling of events, centralized reporting, image transfer and e-mail alerts for reactive and routine maintenance.

PC-Less Presentation



By using a USB memory stick or other storage device, you can use the projector without a computer. Menus are easy to see with a thumbnail display. There is also a slideshow function. This feature also supports the following file types: JPG, PNG, BMP, GIF, AVI, and MOV — frame rate is under 12fps 640 x 480.

PJMessenger



PJMessenger function allows you to send and display text messages and audio alerts on your networked projectors. It is an easy and efficient way to send announcements out to multiple units.

Present Content via LAN



Dukane's suite of networking software allows you to easily send content directly from your PC to the projector via your LAN connection.

Serial Number and Media Access Control Label



A label is affixed to side of projector to more easily access and read the model name, serial number and MAC address while mounted in ceiling use. This is a convenience for installers, end users and auditors for instant accessibility.

Transition Detector and Security Bar



A security sensor located inside the projector recognizes when the projector has been moved. Moving the projector without using the correct PIN code will disable the projector.

Wireless Presentation Compatible



Connect the projector to a computer or your network using the optional USB wireless adapter (part number USBWL11N). The adapter supports IEEE802.11b/g and the latest 11n.

DUKANE CORP

Audio Visual Products
2900 Dukane Drive, St. Charles, Illinois 60174
Toll-free: 888-245-1966 • Fax: 630-584-5156
E-mail: avsales@dukane.com
www.dukane.com/av

* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

** Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

Installing innovation on campus standards nationwide.

Dukane's 8959A features 5,000 ANSI lumens with XGA 1024 x 768 resolution achieving academic excellence in any higher education application. The 8959A combines powerful capabilities with installer-friendly features, inorganic optics, a dust resistant design, and a generous warranty making it ready for the long run. Incorporating Dukane's leading-edge technology, the 8959A also features high contrast




ratio, long lamp life, easy maintenance and is wireless compatible. Vivid colors. Bold graphics. Crisp text. It's easy to see how Dukane's 8959A will enhance the learning experience on college and university campuses nationwide.



Front View



Top View




Side Profile



Rear View

Input/Outputs



- | | | |
|-------------------|---------------------|-----------------------|
| 1. LAN | 8. Computer in 2 | 14. S-Video |
| 2. USB Type A x 2 | 9. Remote Control | 15. Audio in 2 |
| 3. USB Type B | 10. Monitor Out | 16. Audio in 1 |
| 4. HDMI | 11. Microphone | 17. Kensington Lock |
| 5. Audio Out | 12. Component Video | 18. Control (RS-232C) |
| 6. Audio in 3 | 13. Video | 19. Security Bar |
| 7. Computer in 1 | | |

DUKANE CORP

Audio Visual Products
 2900 Dukane Drive, St. Charles, Illinois 60174
 Toll-free: 888-245-1966 • Fax: 630-584-5156
 E-mail: avsales@dukane.com
 www.dukane.com/av

8959A

Accessories and Lenses

Supplied Accessories	Remote control, power cord, computer cable, user's manuals, safety manual, lens cap, security label
Optional Accessories	TB-1 wireless USB tablet, USBWL11N USB wireless adapter, HL02651 laser/wired remote control, MS-1 switcher, MS-1WL wireless multifunction switcher, LCDS2000 soft sided case
Replacement Parts	
Lamp	456-8958H-RJ
Remote Control	HL02881
Filter	MU07791

Projection Throw Chart (In inches)

Screen Size 4:3		Throw Distance	
Diagonal	Width	Min	Max
30	24	34	57
60	48	70	117
80	64	94	157
100	80	118	197
150	120	179	297
200	160	239	396
300	240	360	596

Throw Ratio: 1.5 - 2.5 : 1 (distance : width)

Specifications

Display	Projection Technology	3LCD, 3 chip technology
	Resolution	XGA 1024 x 768
	White Light Output	5,000 ANSI lumens
	Color Light Output	5,000 ANSI lumens
	Colors	16.7 million colors
	Aspect Ratio	Native 4:3 / 16:9 and 16:10 compatible
	Contrast Ratio	3,000 : 1 (using active IRIS)
Lens & Operation	Throw Ratio (distance : width)	1.5 - 2.5 : 1
	Focus Distance	34" - 596"
	Display Size	30" - 300"
	Lens	f = 19 - 32 mm x 1.7 manual zoom, focus & lens shift
	Lamp Wattage	245W
	Expected Lamp Life*	Approximately 3,000 hours (standard mode) 5,000 hours (Eco mode)
	Expected Filter Life**	Approximately 5,000 hours
Compatibility	Speaker Output	16W
	Acoustic Noise Level	35 dB (29 dB in Eco mode)
	Keystone	H: +/- 35° and V: +/- 37.5°
	Computer	VGA, SVGA, XGA, WXGA/SXGA/WXGA+/SXGA+/UXGA (compressed), MAC 16"
	H-Sync	31.5 kHz - 106 kHz
	V-Sync	56 Hz - 120 Hz
	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
Connectors	Component Video	480i, 480p, 576i, 720p, 1080i, 1080p
	HDMI	480i, 480p, 576i, 720p, 1080i, 1080p, Computer signal TMDS Clock 27 MHz - 150 MHz
	Digital Input	HDMI x 1 (HDCP compliant)
	Computer Input 1	15-pin mini D-sub x 1
	Computer Input 2	BNC x 5
	Computer Monitor Output	15-pin mini D-sub x 1
	Video Input	S-Video Composite Video Component Video
Ratings & Warranty	Audio Input	3.5 mm stereo mini jack x 2, RCA jack (L/R) x 1, MIC-in 3.5 mm mini jack x 1
	Audio Output	RCA jack (L/R) x 1
	Network LAN Wired	RJ-45 port (10 base-T / 100 base-TX)
	Network LAN Wireless	USB-A, IEEE802.11 b/g/n - optional wireless adapter required
	USB	Type A x 2 (PC-less presentation, wireless adapter, TB-1) Type B x 1 (USB display or mouse control)
	Control Terminals	9-pin D-sub x 1 (RS-232 control)
	Power Supply	AC100-120V / AC220-240V, 50/60Hz
Connectors	Power Consumption	370W
	Operating Temperature	41°F - 95°F (5°C - 35°C)
	Dimensions (W x D x H)	15.8" x 12.5" x 4.1" (excluding protruding parts) Shipping 19" x 15" x 8"
	Weight	approx. 10.1 lbs. / Shipping 16 lbs.
	Approvals	UL 60950-1 / cUL, FCC Part 15 subpart B class B
	Warranty	Five (5) year limited warranty plus Dukane's 1 year Peace of Mind Loaner Program
	UPC	605194002931

* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

** Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.



DUKANE CORP

Audio Visual Products
2900 Dukane Drive, St. Charles, Illinois 60174
Toll-free: 888-245-1966 • Fax: 630-584-5156
E-mail: avsales@dukane.com
www.dukane.com/av



8959A