

Dukane Webcam

The Dukane WC350 webcam is portable, foldable, and can be used in various applications of usage. For instance, it can work as a live streaming camera, video call camera, as well as video conference camera. With a facial recognition application, it can also be used as a terminal for face verification.



1080P



90° wide field of view



built-in mic



USB plug&play



Associated Devices



Adhesive disc



Tripod



Stretchable clip

Key Features



HD video images

3MP resolution, well apply in scenarios like live streaming, gaming, video conference etc., with fluent streaming video up to 2048X1536@25fps.



With WDR

With WDR (wide dynamic range), you could take high quality images even in a backlighting.



Acoustic sound norm

Built-in noise cancelling microphone, enhance the sound effect, even in a noisy surrounding, your voice could still be heard clearly in the streaming.



Stretchable clip design

Stretchable clip design, can fix camera easily everywhere, and after folding the clip, it can cover the lens protectively, and fit in a size of pocket.

Industrial applications



Individuals: Online live streaming



social: Video call



Enterprises: Video conferencing



Education: Remote video education

Specifications

Sensor	1/3"
Pixels	2048X1536
Pixel size	2.2umX2.2um
Data output type	RAW data 10bits
Output format	MJPEG/YUY2
MJPEG Frame rate	2048X1536@25fps, 1920X1080@25fps,1600X1200@25fps, 1280X1024@25fps,1280X960@25fps,
	1280X720@25fps,1024X768@25fps, 800X600@25fps, 640X480@25fps, 352X288@25fps
	320X240@25fps, 160X120@25fps
YUY2 Frame rate	2048X1536@3fps,1920X1080@5fps,1600X1200@5fps,1280X1024@8fps,1280X960@9fps,
	1280X720@9fps,1024X768@10fps,800X600@20fps,640X480@25fps, 320X240@25fps
	320X240@25fps, 160X120@25fps
SNR	≥40dB
DR	≥100dB
minimum illumination	≥0.1lux
interface	USB2.0
interface velocity	480Mb/S
Rating	5V+/-5%
Power	Max1W (NOLED)
lens type	M12
Camera angle	90°
System	Mac /Linux /Windows XP and above